



Speed

1K water-based wood floor finish. Ideal for time-critical construction sites.

**Fast & rich –
with just 2 coats.**



2-SCHICHT-AUFBAU
2-COAT-SYSTEM



LOBA – Your partner for surface finishing and care.

Why end users are convinced by Speed:

- Long-lasting floor due to protection against scratches and very good resistance to chemicals
- Various design options through the use of additives, e.g. for coloration
- High resistance to soiling, which allows cleaning and care cycles to be extended
- Very low emissions

Why processors are enthusiastic about Speed:

- 2-coat full set-up without primer; the coat thickness corresponds to a 3-coat set-up
- High solids content
- Excellent sandability
- Intensification of the wood color
- Highly resistant to plasticizers from wood floor adhesive
- Low emission, EMICODE® EC2
- Very easy to apply

Special feature

Ideal for time-critical construction sites and immediate results! Thanks to the high coat thickness with only 2 coats, LOBA Speed enables efficient completion, even under tight schedules – projects can typically be completed within a day.

Range of use

Suitable for parquet and wood floors. For normal to heavy traffic, use in residential areas and light commercial use.



Stress level

1 2 3 4 5 6 7 8 9 10

Residential Commercial Extreme

Art. No. 11568

Available in: semi-gloss (5 kg), satin (5 kg)

GISCODE W2+

EMICODE EC2

CONNECTED SYSTEMS

EMISSIONS DANS L'AIR INTERIEUR A+

Ü

Übersicht über die Eigenschaften und die Anwendung des Produktes

Application

- Professionally sand and remove dust from the substrate
- First application of Speed with the Deluxe 120 paint roller
- Intermediate sanding after 4 hours at the earliest with LOBASAND PerforatedPad P180, alternatively sanding grid P180
- Second application of Speed with the roller Deluxe 120
- Consumption rate per application: 120–150 ml(g)/m²

LOBA is always at your side, providing advice and support to ensure your success. Our experienced application specialists will advise you individually on your projects and our competent service team will be on hand quickly if you need practical support directly on site. So you can play it safe right from the start and know who you can rely on at all times.

Do you still have questions? Do not hesitate to contact us.

Please refer to the detailed technical information, processing instructions and recommended finishes.

More information



LOBA GmbH & Co. KG

Leonberger Str. 56–62 | 71254 Ditzingen | Germany | Phone: +49 7156 357-0 | E-Mail: service@loba.de | www.loba.de