



2K Intensive Transparent

High-Solid 2-component oil-based primer for wooden floors.

Emissions

 <p>Loba GmbH & Co. KG Emissionsgeprüftes Bauprodukt nach DIBt-Grundsätzen Z-157.10-192</p>	<p>Approval number Z-157.10-192</p>	<p>According to DIBt (German institute for building technology)</p>
 <p>ÉMISSIONS DANS L'AIR INTÉRIEUR A+</p>	<p>A+</p>	<p>According to French VOC classification</p>

Technical evaluation

<p>GISCODE</p>	<p>Ö40/DD+ (Oils/waxes, solvent-based, dearomatized, oxime free, with isocyanate-based hardener)</p>
----------------	--

Glossar

DIBt

For reasons of health protection, the German Institute for Building Technology (DIBt) requires a general building supervisory approval for all building products used for the treatment and bonding of parquet on site. Certified building materials are marked with the Ü symbol. This obligation to obtain approval has been in force in Germany since 1 January 2011. In order to obtain approval, compliance with emission limits must be proven and the formulations must be disclosed to the DIBt. www.dibt.de

DGALN

The French VOC classification classifies construction products that are permanently processed indoors according to their emissions into emission classes A+, A, B or C, where A+ stands for the best and C for the worst emission class. These construction products have had to be labelled in France since 2012.

GISCODE

The term GISCODE stands for Hazardous Substance Information System Code and was developed by the BG Bau (Employer's Liability Insurance Association for the Construction Industry). It is a labelling system in which products with comparable health hazards are grouped together in product groups. The coding consists of a letter/number combination that uniquely assigns the product to a product group. To obtain specific product information, a product group can be selected on the GISBAU website (= Hazardous Substance Information System of the BG Bau) and detailed hazardous substance information can be found in the appropriate table.

Notes

Notice

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.