

2K Duo

Water-based 2-component polyurethane
finish for wooden floors



2K Duo with improved slip resistance – versatile and proven worldwide

A true universal talent, 2K Duo is available in six different variants. It makes wooden surfaces extremely resistant and is perfectly suitable for a wide range of applications, from event halls to offices and homes. 2K Duo is ideal for almost all types of wood and has been certified as particularly low in emissions according to EMICODE® EC1 Plus.

Why end users are convinced of 2K Duo:

- High resistance to wear
- Excellent resistance to abrasion
- Particularly low in emissions (satin, semi-gloss, and anti-slip variants)
- Available in 4 different gloss levels and 2 anti-slip variants
- All variants offer ideal slip resistance

Why contractors are enthusiastic about 2K Duo:

- Excellent resistance to chemicals and abrasion
- Improved slip resistance: variants gloss, semi-gloss, satin and extramatt
- Safe and easy application
- Extremely easy to mix
- Can be used on various flooring, including colored floors
- Particularly low in emissions, EMICODE® EC1 PLUS ¹⁾
- Part of LOBA Wakol – Connected Systems

Special features

Thanks to its excellent resistance to wear and high level of slip resistance, 2K Duo is ideally suited to flooring subject to heavy traffic.

Range of use

Suitable for parquet, wooden and cork flooring as well as linoleum and PVC coverings. For use in living areas, event halls or offices.

Application

- Thoroughly sand and de-dust the floor
- Prime and allow to dry as specified in the technical data sheet of the primer
- Apply an initial coat of 2K Duo using the Deluxe 120 roller
- Intermediate sanding with the LOBASAND PerforatedPad after at least 8-10 hours. Select the appropriate grain for the variant as specified in the technical data sheet of the product
- Apply a second coat of 2K Duo using the Deluxe 120 roller
- Amount used per coat: 100-120 g/m²



Stress level

1 2 3 4 5 6 7 8 9 10

Residential Commercial Extreme

Art. No. 11466

Available in satin (1 kg, 5 kg), semi-gloss (1 kg, 5 kg), extra-matte (5 kg), gloss (5 kg)

GISCODE W2/DD+ resp. W3/DD+

U **EMICODE** ¹⁾ **EC1** **M1** **CONNECTED SYSTEMS**

EMISSIONS DANS L'AIR INTERIEUR **A+** **DIN 18032**

R9 **6-10°**

¹⁾ satin, semi-gloss

LOBA is always at your side and ensures your success with both advice and action. Our experienced application specialists will advise you personally with your projects. Our competent service team is quickly on hand if you need practical support directly on site. So you can be confident right from the start and know who you can rely on at all times.

Do you have any questions? Please don't hesitate to contact us:

Please always refer to the Technical Data Sheet and set-up recommendations for more detailed instructions.

More Information



LOBA GmbH & Co. KG

Leonberger Str. 56-62 | 71254 Ditzingen | Germany | Tel: +49 7156 357-0 | E-Mail: service@loba.de | www.loba.de