









High Performance. Sustainable. Easy.

1K finish for wooden floors with 2K performance. Based on renewable raw materials.



2K PERFORMANCE



RENEWABLE RESOURCES



25 % REDUCTION

Typical EasyFinish:

- 1K system with 2K performance high resistance to mechanical wear and household chemicals
- Easy and safe to apply, without lap marks
- Based on renewable raw materials*
- 25 % CO₂-reduction on the product compared to the industry average**
- Very low emission: EMICODE® EC1 PLUS
- Free from PFAS, plasticizers and SVHCs
- Suitable for sports floors: achieves in combination with LOBA care products the coefficient of slip resistance according to DIN 18032
- Sustainable container: 100 % recycled plastic



2K PERFORMANCE





Range of use

Suitable for wood and cork floors. For heavy traffic residential areas and commercial use. Meets the slip resistance requirements of DIN 18032 for sports floors when used in combination with LOBA SportCare or LOBA Refresh.

Application

- Prepare and prime surface properly
- Allow the primer to dry as specified
- Apply initial layer by roller
- Drying
- · Intermediate sanding
- · Apply second layer by roller

- 34.5 % renewable carbon content in the dried finish film
- According to EPDLA (European Polymer Dispersion and Latex Association)

LOBA is your reliable partner, supporting you on your path to success. Our expert consultants and service technicians are here to assist you - from project planning to hands-on help at the job site.

Do you have any questions? We look forward to your call or message!

Please always refer to the Technical Data Sheet and application instructions for more details.



Further information